

FEATURES

- Color Mini –Dome CCD SONY Super HAD
- Built in 24 pieces of IR illuminators
- Effective night vision range: up to 20M (60ft)
- Built-in 3.6mm lens
- Low lag, high burn resistance
- No distortion
- Vibration resistance
- Long Life
- Easy to install



SPECIFICATIONS

Image Pick-up Device	1/3" CCD SONY Super HAD
Effective Picture Elements	NTSC: 510H x 492V
Horizontal Resolution	420 Horizontal TV Lines
Minimum Illumination	0.2 LUX @ F2.0
Auto White Balance	Yes
Auto Electric Shutter	NTSC/EIA: 1/60s~1/100,000s
Auto Gain Control	YES
Synchronous System	Internal, Negative sync
Video Output	1Vp-p / 75 Ohms. BNC or F connector
Operating Temp.	-10°C to 50°C (14° F to 122°F)
S/N Ratio	More than 48dB
Gamma Characteristic	0.45
Lens Furnished	3.6mm Board lens F2.0 (Optional: 4.3/6.0/8.0/12mm)
Power Consumption	DC12V (+/-) 10% 1.4 Watt (115mA)
IR LED	24 IR LED
Wave Length	850 nm
Beam Spread	50° / 20°
Projection Distance	20M / 60FT
LED Life	6000 Hours
Auto Power On/Off.	CDS auto control
Power Consumption (IR LED full ON).	DC 12Vdc+/- 10% 3.3 Watt (275mA)