



IPX-ED-24V

IPX-ED-24V

ENVIRONMENTAL DOME ENCLOSURE

This high-quality, environmental enclosure is engineered to protect network pan/tilt video cameras from physical and environmental damage. Durable, compact design facilitates the installation of cameras outdoors while maintaining ideal operating temperature with a thermostatically-controlled heater and fan. Heavy-duty mounting bracket conceals all cabling and can be installed on any vertical surface. Optional pole and corner mount adapters also available. Compatible with many leading brands of IP-based pan/tilt/zoom video surveillance cameras.

SPECIFICATIONS

Construction

- Die-Cast Aluminum Body
- Clear Acrylic Lower Dome

Power Requirement

- 24VAC Input
- Built-in 12VDC 2A Output Terminals

Environmental Rating

- IP66 Certified

Operating Temperature

- -30°C to 50°C (-22° to 122° F)
- 0 to 95% Relative Humidity

Color

- Beige

Heater

- Activates at 0°C (32°F)
- Di-Activates at 10°C (50°F)

Internal Fan

- Activates at 40°C (104°F)
- Di-Activates at 25°C (77°F)

Measurements

- Length13.8 inches
- Width8.6 inches
- Height12.4 inches
- Weight 7.6 lbs.

Optional Accesories

- Pole Mount Adapter
- Corner Mount Adapter
- 24VAC Plug-in Transformer

Supported Cameras

- Axis 213 PTZ
- Canon VB-C50iR
- D-Link DCS-5300
- D-Link DCS-6620
- Hawking HNC800PTZ
- Hawking HNC700PT
- Vivotek PZ6112
- Vivotek PT3112
- 4XEM IPCAMWPTZ
- 4XEM IPCAMWPT

Product specifications and availability subject to change without notice.