




Product Performance

			
Product	MP3004	MP3008	MP3016
Manuf. SKU	NVDMP3004	NVDMP3008	NVDMP3016
Video Card	1 Video Card	1 Video Card w/ 1 extension cards	1 Video Cards w/ 3 extension cards
Video Input	4 channels	8 channels	16 channels
Total Display Rate (NTSC/PAL)	120/100 fps	120/100 fps	120/100 fps
Total Recording Rate (NTSC/PAL)	60/60 fps	80/80 fps	120/100 fps

[top](#) ↑

Features

- ? Display Rate (Total): See chart above
- ? Recording Rate (Total): See chart above
- ? O/S Support: Microsoft Windows® 98SE, Windows® Me, Windows® 2000, and Windows® XP
- ? Support Pan/Tilt/Zoom cameras
- ? Alert on event (Sensor/Relay/Motion Detection). Configurable for each camera
- ? Multi-tasking: Simultaneous monitoring, recording, playback, and remote monitoring
- ? Display Mode: Auto scan with full screen display under 1/4/9/12/16 cameras display mode
- ? Video Search: Sort recorded files by year, month, date, hour, minute, and second. Files can be played consecutively
- ? Event Search: Search recorded files by events (motion, audio, call out, sensor input, relay output, video loss, and alarm recording)
- ? Intelligent Search: Using mask to search motions from massive recorded files
- ? Multiple playback: 1/4/9/16 channels playback in the same time
- ? Backup Mode: Manual backup and schedule backup
- ? Backup Device: Disk Array, Tape Drive, CD-R and ZIP Drive
- ? Alarm Messages: Fax or send alarm message to pagers, mobile, landline phones, mailbox and e-mail.
- ? Remote Transmission: LAN and Internet (via Modem/ADSL/ISDN)
- ? Remote Manager: Remote monitoring, recording, playback, backup, Pan/Tilt/Zoom control, and Center Station function. (Up to 16 servers)
- ? Video Recording Mode: Alarm trigger/Motion Detection/Continuous/Schedule recording/Recycle recording
- ? Masking blank zones under recording mode
- ? Motion Detection: Programmable multiple detection zones for each camera
- ? Access control protected by passwords
- ? Remote backup ensures data security

Features subject to change without notice

[top](#) ↑

Specifications

- ? VGA Output Resolution: 1024X768
- ? Video Compression: Motion JPEG
- ? Image Resolution: 320X240 or 640X480pixels
- ? Sensor Input/Relay Output Device: Up to 4 inputs and 3 outputs
- ? Recorded Video Format: DSS
- ? Recorded Audio Format: WAV
- ? Warranty: One year limited parts & labor
- ? Compliance: FCC Class A

[top](#) ↑

System Requirements

- ? CPU: Pentium® III 800 mhz or above
- ? RAM: 128MB (recommend 256MB)
- ? Motherboard: Intel®815/845 chipset
- ? HDD: 80GB or above
- ? VGA: 32MB RAM (recommend 64MB)
- ? Operating System: Windows®98SE/ME/2000/XP (recommended Windows 2000)
- ? Video Input: 4/8/16 NTSC/PAL cameras (BNC connector), Support PTX Cameras (Cameras not included)

[top](#) ↑

Package Includes

- ? Video Capture Card (Each video capture card with 4 video inputs)
- ? Extension Card (only for MP3008 & MP3016)
- ? User Manual
- ? MP3000 Software CD (Including Driver, Application Software, and User's Manual)